

LIGHT KIT

OWNER'S MANUAL

MODEL: M2027XX

All electrical connections must be in accordance with local codes, ordinances, or national codes. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified electrician. Before starting installation, disconnect the power by turning off the circuit breaker or removing the fuse at fuse block. Turning power off using fan switch (speed control on/off) is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by the person (s) caring for and operating the unit.

1. Remove the switch housing cover from the switch housing. Remove the plug from the switch housing cover.
2. Attach the light kit to the switch housing by feeding the light kit wires (black and white) through the hole of switch housing and then screw it onto the switch housing by nut & lock washer. Be sure it is tight enough to prevent light kit from vibrating loose. (Fig. 1)
3. Locate the terminal block in the switch housing for light wire connection; loose the screws on the terminal block, insert the light wire to each terminal block and re-tighten the screws loosened previously, make sure the white wire from the light kit connected to the white wire from switch housing, and black wire from light kit connected to the blue wire from switch housing.
4. Carefully push all wires back into the switch housing. Attach the light kit fitter by aligning its keyhole slots with the three screws holes and reversing switch on the side of switch housing. Tighten the three screws. (Fig.2)
5. Install 2 x 9 watts LED bulbs. (included)
6. Mount the glass shade to the light fixture by unscrewing partway the thumbscrews on the light fixture, inserting the glass, then gently tightening the thumbscrews by hand evenly to the glass. DO NOT OVER TIGHTEN. (Fig. 3)
7. Restore power and your light kit is ready for operation.

