

LIGHT KIT

OWNER'S MANUAL

MODEL: M2028XX

All electrical connections must be in accordance with local codes, ordinances, or national codes. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified electrician.

Before starting installation, disconnect the power by turning off the circuit breaker or removing the fuse at fuse block. Turning power off using fan switch (speed control on/off) is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by the person (s) caring for and operating the unit.

1. Remove and discard the finial from the switch housing.
2. Attach the light kit to the switch housing by feeding the light kit wires (black and white) through the hole of switch housing and then screw it onto the switch housing by nut & lock washer. Be sure it is tight enough to prevent light kit from vibrating loose. (Fig. 1)
3. Locate the terminal block in the switch housing for light wire connection; loose the screws on the terminal block, insert the light wire to each terminal block and re-tighten the screws loosened previously, make sure the white wire from the light kit connected to the white wire from switch housing, and black wire from light kit connected to the blue wire from switch housing. (Fig. 1)
4. Remove the three screws from the mounting plate. (Fig. 2)
5. While holding the light kit assembly under your fan, snap together the wire connection plugs. (Fig. 2)
6. Carefully push all wires back into the switch housing. Install the light kit assembly onto the mounting plate with the three screws provided. Be sure to tighten all screws. (Fig. 2)
7. Install 3 x 7 watt LED bulbs (included). (Fig. 2)
8. Remove the decorative nut cap and metal nut from the light kit stem. Raise the light frame up against the light kit assembly, place the metal nut over the light kit stem and turn it clockwise until it locks up against the light kit stem. (Fig. 3)
9. Secure the cap and decorative nut.
10. Restore power and your light kit is ready for operation.

