



ASSEMBLY INSTRUCTIONS

1. Carefully unpack and identify all parts referring to illustration for parts identification.
2. Turn the power to the installation point OFF.
3. Unravel the supply power and ground wires and pass them through the center rods(I), center rod(J), loop (K) and canopy (M).
4. Thread the bottom of the support column (F) onto the protruding nipple of the bottom assembly (E). Place the top assembly (G) onto the support column (F), and secure with screws (H). Install the stem (B) onto the nipple of the socket assembly (A).
5. Install the stem (B) onto the top assembly (G). Hand tighten until snug.
6. Thread the bottom of center rods (I) onto the top assembly (G). Repeat the process for remaining center rods(I) and center rod(J) as shown in the diagram, until snug.
7. Install loop (K) onto the top of the center rod(J).
8. Use carabiner (L) to connect loop (K) to the loop on the canopy (M) and twist the locking mechanism to secure.
9. Carefully attach the hook of the bead string (C) and crystal (D) hook to the bottom assembly (E) and top assembly (G). Repeat the process for remaining bead strings(C) and crystals(D).
10. Refer to the additional installation instructions included with the product for wiring and installation.
11. Install proper bulbs (not provided) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
12. Restore power to the installation point and retain this sheet for future reference.