



ASSEMBLY INSTRUCTIONS

1. Carefully unpack and identify all parts referring to illustration for parts identification.
2. Turn the power to the installation point OFF.
3. **Unfold support arms of the fixture body (A) to the proper locations.**
4. **Remove the finial (L) and hex nut (K) from the nipple (I), then place the cap (H) over the coupling. Thread the beaded end of the nipple (I) onto the coupling on the fixture body (A). Hand-tighten until snug.**
5. **Place the bottom assembly (J) over the nipple (I). Secure with the previously removed hex nut (K) and finial (L). Hand-tighten until snug.**
6. Unravel the supply power and ground wires and pass them through the center holes of column (B), rods (C), rod (D), loop (E) and canopy (F).
7. Thread the bottom of column (B) onto protruding nipple at the top of fixture body (A). Repeat process for remaining rods (C), rod (D). Hand tighten until snug.
8. Install the loop (E) into the top of rod (D).
9. Use the carabiner (G) to connect the loop (E) to the loop on the canopy (F) and twist the locking mechanism to secure.
10. Refer to the additional installation instructions included with the product for wiring and installation.
11. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
12. Restore power to the installation point and retain this sheet for future reference.